Distributed by:

JAMECO® ELECTRONICS

www.Jameco.com ✦ 1-800-831-4242

The content and copyrights of the attached material are the property of its owner.

RELIABILITY PREDICTION

Model : SP-200 Data:2000-01-11

Style	Part Type	Q'ty	λ_g	π_Q	λ_{eg}	%
9.1	Resistor-Film, Insulated (RL)	51	0.003700	10	1.887000	34.695
9.1	Resistor-Wirewound Power (RW)	1	0.008500	10	0.085000	1.563
9.1	Resistor-Film, Variable (RVC)	1	0.040000	10	0.400000	7.354
9.1	Resistor-Thermistor (RTH)	2	0.001400	10	0.028000	0.515
10.1	Capacitor-Metal, Plastic (CH)	5	0.000510	10	0.025500	0.469
10.1	Capacitor-Ceramic(Gen.) (CK)	19	0.001700	10	0.323000	5.939
10.1	Capacitor-Aluminum Dry (CE)	13	0.001300	10	0.169000	3.107
6.1	Diode-Switching	12	0.000940	8	0.090240	1.659
6.1	Diode-Fast Recovery Power Rectifier	5	0.023000	8	0.920000	16.915
6.1	Diode-Power Rectifier / Schottky Power	4	0.002800	8	0.089600	1.647
6.1	Diode-Voltage Ref/Reg. (Avalanche & Zener)	6	0.003300	8	0.158400	2.912
6.1	Diode-Transient Suppressor/Varistor	3	0.002900	8	0.069600	1.280
6.10	Diode-Thyristor/SCR	1	0.002500	8	0.020000	0.368
6.3	Transistor-NPN/PNP	1	0.000150	8	0.001200	0.022
6.3	Transistor-Power NPN/PNP	1	0.005700	8	0.045600	0.838
6.4	Transistor-MOSFET	2	0.014000	8	0.224000	4.118
6.11	OPTO-isolator	2	0.027000	8	0.432000	7.943
6.11	OPTO-Emitter	1	0.000470	8	0.003760	0.069
5.1	Linear Microcircuits	3	0.009500	10	0.285000	5.240
11.1	Transformer Switching	1	0.000610	3	0.001830	0.034
11.2	Coil Fixed inductor or choke	4	0.000032	3	0.000384	0.007
15.1	Connector- Rectangular	1	0.050000	2	0.100000	1.839
17.1	Single Connections-Reflow solder	370	0.000069	1	0.025530	0.469
17.1	Fuses Clip-Clip Termination	2	0.000120	1	0.000240	0.004
22.1	Fuses	1	0.010000	1	0.010000	0.184
16.1	Plated Through Hole Circuit Boards	1	0.022000	2	0.044000	0.809
Total Failure rate:					5.438884	100%

- **Data Base: MIL-HDBK-217F ,Notice 2, Parts Count**
- **Env.: GB**
- **Exclude: FAN**

MTBF: 183861.25 **hrs**

Approved by: David Wang Compiled by: Kim Tseng .